

Product Code: RTS107

Information: Cool Touch Thermostatic Shower

Mixer with Riser Rail Kit

ConstructionBrass Body (CuZn38Pb18)FinishesChrome plated to BS EN 248

Product Type Contemporary

Water Pressure Min. 0.5 bar, Max. 6.0 bar

Plumbing Systems Suitable for all plumbing systems, preferably balanced.Min. supply pressure

differential requirement is 5:1

Standards Complies with BSEN 1111

Certification Manufactured to comply with WRAS, TMV2

CartridgeThermostaticFittingS-unions

Valve Integrate diverter ceramic valve

Check valve 0.5-10 gpm

Packaging 84 x 44 x 45cm / carton (5 boxes / carton)


Guarantee10 years against manufacturing faults (excluding serviceable parts).Additional Information1.Temperature: Pre-set 38°C, with push button override to 48°C.2.Automatic shut off in the event of hot or cold water supply failure.

3.Shower head : Chrome , Ø200mm, ABS 4.Shower handset : Chrome , 3 mode, ABS 5.Shower hose : 1.5m, stainless steel

6.Riser rail: Stainless steel; telescopic adjustable height riser rail

Overall Dimensions:





Flow Rates (Litres per minute)

System Pressure	0.1 Bar	0.2 Bar	0.3 Bar	0.5 Bar	1.0 Bar	1.5 Bar	2.0 Bar	3.0 Bar	4.0 Bar	5.0 Bar
VM107	2.4	3.8	-	6.7	10.9	-	-	17.0	-	-

All Dimensions are in millimetres. The information contained on this page was correct at date of issue. Fitting dimensions are provided as a guide only. Some variation may occur due to manufacturing tolerances. We pursue a policy of continuing improvement in design and performance of our products and so reserve the right to change specifications without prior notice.